

K50 & K65 MOBILE AREA LIGHTING SYSTEMS





The K65 and K50 range of portable LED Floodlighting is the perfect high power, indoor and outdoor lighting solution for both task and area illumination. These units do not need to rely upon diesel generators as a primary power source.

This mobile range of site lighting can be powered from:

- 110V and 240V mains power
- Ancillary battery
- LPG, Hydrogen or Diesel generator

With the ability to mobilise this lighting system via a single person operation, power capable of being supplied by multiple diesel free energy sources and illumination to rival any traditional mobile tower light, the K65 and K50 floodlights provide a lighting solution to provide the following:

Features & Benefits

- Rescued noise pollution
- Reduced carbon emissions
- Reduced fuel consumption
- Reduced set up and management time
- Reduced cost
- 6000 sqm of illuminated space guaranteed
- Auto start/stop light sensor

- Mast safety system
- Forklift pockets for easy handling
- 4/6 x 100W LED Floodlights providing instant bright lights with no wait time
- Onboard levels for guidance during stabilisation

0333 3002345

sales@pickeringshire.co.uk

Specifications

K50 DIMENSIONS (STOWED)		
HEIGHT	1950 mm	
WIDTH	830 mm	
LENGTH	1090 mm	
WEIGHT	240 kg	

LIGHTING & MAST	K50/K60
360° LIGHTING @20 LUX	Up to 7396 m ²
LUMENS 200W	28,000 per light head
LUMENS 240W	40,800 per light head
MAST TYPE	Automatic
LIGHT DIRECTION	180/360°

K50 DIMENSIONS (OPERATING MODE)		
HEIGHT	5200 mm	
WIDTH	3100 mm	
LENGTH	2370 mm	
WEIGHT	240 kg	

K65 DIMENSIONS (STOWED)	
HEIGHT	1950 mm
WIDTH	830 mm
LENGTH	1090 mm
WEIGHT	250 kg

K65 DIMENSIONS (OPERATING MODE)		
HEIGHT	6620 mm	
WIDTH	3100 mm	
LENGTH	2370 mm	
WEIGHT	250 kg	

LIGHTING & MAST	K50/K60
360° LIGHTING @20 LUX	Up to 7396 m^2
LUMENS 200W	28,000 per light head
LUMENS 240W	40,800 per light head
MAST TYPE	Automatic
LIGHT DIRECTION	180/360°



0333 3002345 sales@pickeringshire.co.uk